

Pressure cooker test Chamber ETSP-PCT series

Technical Specification

Model	Internal dimensions	External dimensions	Useful capacity
ETSP-PCT 48	350(φ) × 500(D)mm	850 × 900 × 1260 (W × D × H) mm	48 liters
ETSP-PCT 70	450(φ) × 450(D)mm	950 × 850 × 1360 (W × D × H) mm	70 liters
ETSP-PCT 183	650(φ) × 600(D)mm	1150 × 1000 × 1560 (W × D × H) mm	183 liter

❖ **Note** Different size of chambers are available on user's demand

- **Controller** 5.7"± touch screen LCD controller,
2Ch control, multi input, multi output, alert output,
stores up to 100 patterns Max. 2,400 segments (Max.100seg/pattern)
RS232/RS485 data interface
- **Safety devices** Leakage breaker, Circuit breaker, Overheat protector for chamber,
Over heat protector for steam tank, Water low level switch, Electrical over current relay,
Emergency shut off switch, Pressure relief valve

Included accessories

- End of cycle, Hi & low limit audible alarm
- Real time clock (Auto start)
- 12 feed through power terminals
- Two stainless steel shelves
- Caster for moving
- Cartridge type water reservoir with connector.
- Hard copy/soft copy instruction and maintenance manual

Options

- Chart recorder
- Additional hermetic terminals for power application or for thermocouple
- Additional shelf
- Customization available