

Temp. & Humidity Chamber **ETSP-TH** series

Technical Specification

Model	Internal dimensions	External dimensions	Useful capacity
ETSP-TH 60	300 × 400 × 500 (W × D × H) mm	900 × 900 × 1500 (W × D × H) mm	60 liters
ETSP-TH 150	500 × 500 × 600 (W × D × H) mm	1100 × 1000 × 1600 (W × D × H) mm	150 liters
ETSP-TH 500	700 × 700 × 800 (W × D × H) mm	1300 × 1100 × 1800 (W × D × H) mm	392 liters
ETSP-TH 1000	1000 × 1000 × 1000 (W × D × H) mm	1600 × 1500 × 2100 (W × D × H) mm	1000 liters

❖ **Note** Different size of chambers are available on user's demand.

- **Controller** Programmable type TFT color LCD 5.7" controller (Max. 120 patterns, Max. 1,200 profile)
- **CFC free refrigerant**
- **Safety devices** Leakage breaker, circuit breaker, over heat protector, refrigerator high and low pressure switch, Water low level switch, compressor built-in protector, pressure relief port, Electrical over current relay.

Included accessories

- Shelves
- Viewing window (heater wire including, reinforced window) and interior light
- Cable port and rubber plug
- Caster for moving
- Cartridge type water reservoir with connector

Options

- Dry air supplier for low humidity control
- Chart recorder
- Dust filter for condensing coil
- Additional port hole and rubber plug
- Additional shelves
- Oven networking connection system (RS422/RS485)
- Customization available